

# Binder FS HARDENER

This product is classified as hazardous according to criteria of NOHSC

## Section 1 – Identification of the Material and Supplier

**PRODUCT (MATERIAL) NAME:** Binder FS HARDENER

**OTHER NAMES:**

**RECOMMENDED USES:** Hardener component of 2 part epoxy flooring system

**SUPPLIER NAME/ADDRESS:** ESS Earth Sciences, 141 Palmer St, Richmond VIC 3121

**TELEPHONE NUMBER:** (03) 8420 8999

**FACSIMILE NUMBER:** (03) 8420 8900

**EMERGENCY PHONE NUMBER:** (03) 9701 3955

**HOURS:** 0800-1700 Mon-Fri

## Section 2 – Hazards Identification

**HAZARD CLASSIFICATION:** Classified as a **HAZARDOUS SUBSTANCE** according to criteria of NOHSC.

Classified as **DANGEROUS GOODS** according to criteria of ADG Code.

**RISK PHRASES:**

**R20/21/22:** Harmful by inhalation, in contact with skin and if swallowed.

**R34:** Causes burns

**R42/43:** May cause sensitisation by inhalation or skin contact.

**R51/53:** Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**SAFETY PHRASES:**

**S24/25:** Avoid contact with the skin and eyes.

**S26:** In case of contact with eyes, rinse immediately with plenty of water and contact a doctor or Poisons Information Centre on 13 11 26 (Australia-wide).

**S28:** After contact with skin, wash immediately with water (and soap if available)

**S36/37/39:** Wear suitable protective clothing, gloves and eye/face protection.

**S61:** Avoid release to the environment.

## Section 3 – Composition / Information on Ingredients

### INGREDIENTS:

Chemical Name:	Proportion:	CAS Number:
Isophoronediamine	10 – 30 %	[2855-13-2]
Benzyl alcohol	30 – 60 %	[100-51-6]
N-aminoethylpiperazine	1 – 10 %	[140-31-8]
Triethylenetetramine	10 – 30 %	[112-24-3]

Balance of formulation consists of ingredients below cut-off rates or ingredients determined not to be hazardous.

## Section 4 – First Aid Measures

**INHALATION:** If inhaled, remove patient from contaminated area to fresh air – avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Lay patient down in a comfortable position, keep warm and rested. Seek medical attention if further symptoms develop. If not breathing, clear airway and apply artificial respiration.

**INGESTION:** If swallowed, DO NOT induce vomiting. Rinse mouth with plenty of water. Seek immediate medical advice from a doctor or the Poisons Information Centre (13 11 26 Australia-wide).

**SKIN:** If skin or hair contact occurs, remove all contaminated clothing and wash before reuse. Flush skin and/or hair with running water and soap if available. Seek medical assistance if irritation persists.

**EYES:** If product comes into contact with eyes, hold eyelids apart and flush the eye continuously with fresh running water. If pain persists or recurs seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

**FIRST AID FACILITIES:** Eye wash and normal washroom facilities.

**ADVICE TO DOCTOR:** Treat symptomatically. **POISON INFORMATION CENTRE** – 13 11 26 Australia-wide. This product is corrosive.

## MATERIAL SAFETY DATA SHEET – PAGE 2 OF 4

### Section 5 – Fire Fighting Measures

<b>EMERGENCY PROCEDURES:</b>	Product may be slippery when spilt – avoid accidents by cleaning up any spills immediately. Wear gloves, protective goggles and appropriate protective equipment to avoid eye and skin contact. Isolate and contain spill and soak up with inert material such as clay or sand. Prevent by any means possible the material from entering storm water drains, waterways, basements or workpits. Collect in suitable containers and ensure these are correctly labelled. Ensure area is thoroughly ventilated before recommencing work.
<b>METHODS AND MATERIALS FOR CONTAINMENT AND CLEAN UP:</b>	Contain and collect spills as detailed above. Refer to State Land Waste Management Authority for disposal considerations.

### Section 7 – Handling and Storage

<b>PRECAUTIONS FOR SAFE HANDLING:</b>	Wear protective goggles or face shield and rubber gloves and barrier cream to prevent eye and skin contamination. Contact lenses pose a special hazard as they may absorb irritants. Suitable protective clothing, PVC gloves and boots should be worn. Use in a well ventilated area, preferably outdoors. General exhaust is normally adequate. If risk of overexposure exists, wear SAA approved dust respirator.
<b>CONDITIONS FOR SAFE STORAGE:</b>	Store in accordance with AS 3780-1994: The storage and handling of corrosive substances; and AS1940: The storage and handling of flammable and combustible liquids.
<b>STORAGE:</b>	Store in a cool, dry, well-ventilated area out of direct sunlight. Store away from strong acids and oxidising agents.
<b>INCOMPATIBILITIES:</b>	No restrictions.

### Section 8 – Exposure Controls / Personal Protection

<b>NATIONAL EXPOSURE STANDARDS:</b>	No exposure standards have been established for this product by NOHSC. No exposure limits have been established for individual constituents.
<b>BIOLOGICAL LIMIT VALUES:</b>	Not established for the product.
<b>ENGINEERING CONTROLS:</b>	If used in limited ventilation, ensure adequate ventilation to maintain exposure levels are kept below standards, by using a local exhaust. Keep containers closed when not in use.
<b>PERSONAL PROTECTION:</b>	Avoid unnecessary contact as good work practice. Wash contaminated clothing and protective equipment before storing and reuse. Wash hands before eating, smoking, or using the toilet.
<b>RESPIRATORY PROTECTION:</b>	It is usually safe not to use respiratory protection. However, where engineering controls are not effective in controlling airborne exposure, the use of a mask or other device is appropriate. For assistance in selecting suitable equipment consult AS/NZ1715.
<b>EYE PROTECTION:</b>	Eye protective measures are normally necessary, and are suggested when using this product. Consult AS1336 and AS/NZ1337.
<b>PROTECTIVE GLOVES:</b>	Rubber, PVC or other protective gloves are necessary, and desirable, especially if this product is being used frequently or for lengthy periods. Consult AS2161 for guidance.
<b>CLOTHING:</b>	Clean overalls should be worn, preferably with an apron. Consult AS2919 for clothing guidance.
<b>SAFETY FOOTWEAR:</b>	Wearing safety boots is advisory. Consult AS/NZ2210 for advice on Occupational Protective Footwear.

# MATERIAL SAFETY DATA SHEET – PAGE 3 OF 4

## Section 9 – Physical and Chemical Properties

**APPEARANCE (COLOUR, PHYSICAL FORM, SHAPE):**

**ODOUR:** Amber thin liquid  
**SOLUBILITY:** Strong amine odour  
**VAPOUR DENSITY:** Insoluble  
**MELTING POINT:** Not available  
**FREEZING POINT:** Not applicable  
**FLASH POINT:** Not available  
**LOWER FLAMMABLE LIMIT:** > 62°C  
**VOLATILE ORGANIC COMPOUNDS (VOC) CONTENT:** Not established

**VAPOUR PRESSURE:** Negligible  
**BOILING POINT:** Not available  
**SPECIFIC GRAVITY:** 1.0 – 1.1  
**UPPER FLAMMABLE LIMIT:** Not established  
**AUTOIGNITION TEMPERATURE:** Unknown  
 Not stated

## Section 10 – Stability and Reactivity

**CHEMICAL STABILITY:** Stable under normal conditions  
**CONDITIONS TO AVOID:** Keep away from strong acids and oxidising agents.  
**INCOMPATIBLE MATERIALS:** No restrictions  
**HAZARDOUS DECOMPOSITION PRODUCTS:** On burning may emit toxic fumes, including carbon monoxide, amines, ammonia and nitrogen oxides.  
**HAZARDOUS REACTIONS:** None

## Section 11 – Toxicological Information

**TOXICOLOGY INFORMATION:** No toxicity data is available for this product.

**HEALTH EFFECTS FROM THE LIKELY ROUTES OF EXPOSURE:**

**INHALATION:** Vapour or mist is irritating to the upper respiratory tract and may cause sensitisation. Inhalation of vapour may aggravate pre-existing conditions such as asthma, bronchitis or emphysema. Acute effects may be chest and nasal irritation with coughing, sneezing, headache and nausea. Hazard increases at elevated temperatures.

**INGESTION:** Harmful and highly irritating if swallowed. Swallowing may result in nausea, vomiting, abdominal pain and diarrhoea. May cause chemical burns to the mouth, throat and oesophagus, with extreme discomfort and pain. Considered an unlikely route of entry in commercial/industrial environments.

**SKIN:** Prolonged exposure is highly irritating and may cause drying and cracking of the skin. Material is corrosive and can cause chemical burns. Capable of causing dermatitis and sensitisation resulting in hives, rash, itching or swelling of extremities. Toxic effects may result from skin absorption. Sensitisation may appear after repeated symptom-free exposures. Open cuts, abraded or irritated skin should not be exposed to this material. This material may accentuate pre-existing skin conditions.

**EYES:** Highly irritating to the eyes and is capable of causing pain and corneal burns. If not promptly treated, can lead to permanent eye injury.

**CHRONIC EFFECTS:** May cause sensitisation in susceptible individuals by skin contact or inhalation. Repeated or prolonged skin contact may result in allergic contact dermatitis.

## Section 12 – Ecological Information

**ECOTOXICITY:** Not available  
**PERSISTENCE AND DEGRADABILITY:** Not available  
**MOBILITY:** Not available  
**ENVIRONMENTAL PROTECTION:** Product is toxic to aquatic organisms, and may cause long-term adverse effects in the aquatic environment. Avoid contaminating waterways.

## Section 13 – Disposal Considerations

**DISPOSAL METHODS AND CONTAINERS:** Refer to State Land Waste Management Authority. Empty containers must be decontaminated. Normally suitable for disposal at approved land waste site.

## MATERIAL SAFETY DATA SHEET – PAGE 4 OF 4

### Section 14 – Transport Information

This material is a Class 8 – Corrosive Substance according to the Australian Code for the Transport of Dangerous Goods. Class 8 Goods are incompatible in a placard load with any of the following:

- Class 1, Explosives
- Class 4.3, Dangerous When Wet substances
- Class 5.1, Oxidising Agents and Class 5.2, Organic Peroxides
- Class 6, Toxic Substances (where the toxic substances are cyanides and the corrosives are acids)
- Class 7, Radioactive Substances
- and are incompatible with food and food packaging in any quantity.

**UN NUMBER:** 2735

**UN PROPER SHIPPING NAME:** Corrosive Liquids N.O.S.

**DANGEROUS GOODS CLASS:** 8

**SUBSIDIARY RISK:** None assigned

**PACKING GROUP:** III

**SPECIAL PRECAUTIONS PER USER:**

Keep containers tightly sealed, store in a cool, dry, well ventilated place out of direct sunlight. Keep away from strong acids and oxidising agents.

**HAZCHEM CODE:** 3X

#### Air transport

*IATA-DGR:*

UN/ID No.: UN 2735

Class: 8

Packaging group: III

Packing instruction (cargo aircraft): 820

ADR/RID-Labels: 8

Proper shipping name: AMINES, LIQUID, CORROSIVE, N.O.S.

Amines, liquid, corrosive, n.o.s. (Benzene-1,3

dimethaneamine(MXDA)/Trimethylhexamethylenediamines)

contains: (TRIMETHYLHEXAMETHYLENEDIAMINES)

Shipment per 49 CFR 171.11//NAERG Guide No:153

### Section 15 – Regulatory Information

**POISON SCHEDULE:** S5

**OHS:** Unregulated

**ENVIRONMENTAL:** Unregulated

**ADDITIONAL NATIONAL AND/OR INTERNATIONAL REGULATORY INFORMATION:**

Unregulated

### Section 16 – Other Information

**DATE OF PREPARATION OR LAST REVISION OF MSDS:**

7<sup>th</sup> April 2021

**CONTACT POINT:** ESS Earth Sciences

(03) 8420 8999

**LITERATURE REFERENCES / SOURCES OF DATA:**

Material Safety Data Sheets from Suppliers

List of Designated Substances – Worksafe Australia (on-line)

Australian Dangerous Goods Code 6<sup>th</sup> Edition

Standard for the Uniform Scheduling of Drugs and Poisons No 19

The information presented herein has been compiled from sources considered to be dependable and is accurate to the best of seller's knowledge, however seller makes no warranty whatsoever, expressed, implied, or of merchantability regarding to the accuracy of such data or the results to be obtained from the use thereof. Seller assumes no responsibility for injury to the buyer or third persons or for any damage to property. Buyer assumes all risks.